SINCE 1997








CONVERTING SOLUTIONS








CONVERTING SOLUTIONS






EDM is a high performance and high productivity doctor machine, capable to run a wide range of substrates, mainly paper based from 140 up to 460 gsm.

The machine has a set of options developed with the last technologies focused on four main vectors :

Safety: Machinery directive 2006/42/EC


Inspection :

Several optional solutions available for a correct adjustment of inspection system to the operation needs



Splice: Aseptic splice

Handling: Easy reel Handling and machine operationability



SAFETY



INSPECTION





SPLICE

HANDLING




Ecoline Doctor Machine

SINCE 1997

MACHINE OPTIONS





EDM


Customization:

With many options available we can supply the right product for your needs

MACHINE SPECIFICATIONS



	Line Speed up to 1200m/min (4000 ft/min)
	Reel Diameter (3,5inch) 90mm < Ø < 1350mm (53 inch)
	Core inner Diameter (2,8 inch) 70mm < \emptyset < 300mm (11,8 inch)
	Normal ramp time up to 13s
	Protective stop time ramp time Up to 5s
	Web Tension (27lbf) 120N < T < 720N (162 lbf)
	Web Width (4,1 inch) 105mm < W < 380mm (15 inch)



Max. reel weight 525 kg (1160 lb)

Web grammage


(0.0286 lb/ft2) 140gsm < WG < 460gsm (0.0942 lb/ft2)

Web thickness

(0,007 inch) 0,176mm < t < 0,678mm (0,027 inch)

Web Compensation

+/- 25mm (+/-1 inch)



Ecoline Doctor Machine

